



Model	Capacity (#/Hr.)		Storage		Storage Tank		Deserator		Dimensions			Water Inlet	Over-flow	Steam Inlet	Weight - Lbs.	
	Cu. Ft.	Gallons	Dia.	S.S.L.	Dia.	S.S.L.	A	B	C	Shipping	Operating				Flooded	
5SS	5,000	13	30"	4'-0"	25"	25"	6'-3"	4'-3"	5'-11"	2-1/2"	1"	2-1/2"	1,100	2,000	2,900	
10SS	10,000	26	30"	6'-8"	24"	25"	9'-0"	4'-3"	5'-11"	2-1/2"	1"	3"	1,300	3,000	4,050	
15SS	15,000	40	36"	6'-0"	24"	28"	8'-6"	4'-9"	6'-9"	2-1/2"	2"	4"	1,600	4,150	5,000	
20SS	20,000	53	40"	8'-0"	24"	28"	10'-6"	4'-9"	8'-9"	2-1/2"	2"	5"	1,800	5,200	6,150	
30SS	30,000	80	42"	9'-1"	24"	28"	11'-9"	5'-3"	7'-3"	2-1/2"	2"	6"	2,500	7,550	8,600	
45SS	45,000	120	42"	13'-11"	30"	30"	16'-9"	5'-3"	7'-6"	2-1/2"	2"	8"	3,100	10,650	12,250	
60SS	60,000	160	48"	13'-4"	30"	30"	16'-3"	5'-9"	8'-0"	3"	3"	8"	4,300	14,350	16,000	
75SS	75,000	200	48"	17'-0"	36"	30"	20'-0"	5'-9"	8'-6"	3"	4"	10"	5,550	18,000	20,250	
90SS	90,000	240	54"	15'-5"	36"	30"	18'-9"	6'-3"	9'-0"	3"	4"	10"	5,600	20,900	23,050	
120SS	120,000	320	54"	21'-0"	36"	30"	24'-3"	6'-3"	9'-6"	4"	4"	12"	6,600	26,750	29,350	
150SS	150,000	400	60"	21'-2"	42"	30"	24'-9"	6'-9"	10'-3"	4"	6"	12"	8,350	33,600	36,900	
180SS	180,000	480	60"	21'-8"	42"	42"	21'-6"	7'-9"	12'-3"	6"	6"	14"	7,900	38,200	41,400	
210SS	210,000	560	72"	20'-10"	48"	42"	25'-0"	7'-9"	12'-3"	6"	6"	16"	9,450	49,800	56,100	
240SS	240,000	640	72"	24'-0"	48"	42"	28'-3"	7'-9"	12'-3"	6"	6"	16"	9,450	49,800	56,100	
270SS	270,000	720	84"	27'-3"	48"	42"	31'-6"	7'-9"	12'-3"	6"	6"	18"	10,200	55,650	62,350	
300SS	300,000	800	84"	22'-0"	54"	42"	26'-6"	8'-9"	13'-3"	8"	*6"	18"	11,650	62,150	69,200	
330SS	330,000	880	84"	24'-4"	54"	42"	28'-9"	8'-9"	13'-3"	8"	*6"	20"	12,500	68,050	75,450	
360SS	360,000	960	84"	26'-8"	60"	42"	31'-0"	8'-9"	13'-3"	10"	*6"	20"	13,350	73,950	82,600	
390SS	390,000	1040	84"	29'-0"	60"	42"	33'-6"	8'-9"	13'-3"	10"	*6"	20"	14,200	79,850	88,900	
420SS	420,000	1120	90"	26'-0"	60"	42"	30'-6"	9'-3"	13'-9"	10"	**6"	24"	16,700	87,350	96,250	

- NOTE:**
1. Storage capacities based on 10 minutes, other capacities available upon application.
 2. Water outlet(s) vary with application.
 3. Weights apply to vessel only, and do not include accessories.
 4. All dimensions, weights, volumes, etc. are approximate and subject to change without notice.
 5. Overflow trap sizing based on five P.S.I.G. operation pressure except:
 - * P.S.I.G. operating pressure
 - ** 15 P.S.I.G. operating pressure